



PRESSURE TEST			
DN	Pressure Rating(PN)	Hydra--Test Pressure(MPa)	
		Body	Seat
100--600	16	2.4	1.76



Material Specification

1	FLANGED BODY	EN-GJS-450-10
2	STUD	SS316
3	FLANGED SPIGOT	EN-GJS-450-10
4	RETAINER	EN-GJS-450-10
5	RING	EPDM
6	BOLT AND NUT	SS316

NO	DN	D2	D4	L1	L2	D(Ø)	N	d(Ø)	n	W(kg)
1	DN100	118	180	200	330	M16	4	M12	4	16
2	DN150	170	240	200	340	M20	4	M12	4	24
3	DN200	222	295	220	350	M20	4	M12	4	32
4	DN250	274	355	230	380	M24	4	M12	6	48
5	DN300	326	410	230	400	M24	4	M12	6	62
6	DN400	429	525	260	420	M27	4	M14	8	106
7	DN500	532	650	280	460	M30	4	M14	10	175
8	DN600	635	770	300	490	M33	4	M14	10	235

Note:

Both FBE coating and Rubber gasket with WRAS certificated.
Flange dimensions according to EN1092 PN16, flange thickness is based on our current mould.

***Technical improvements reserved the right to DELTA.

Total Drawing No.:

ALM-DJ-16-000

Sud-Drawing No.:

NAME:
Dismantling Joint
PN16
FBE coating
RAL No.5015

Ref. No.: 10123

SUPPLIER:
XUZHOU DELTA

