



Specificate		
Nominal pressure (MPa)		1.0 or 1.6
Testing pressure (MPa)	Body	2.4
	Seal	1.76
Working pressure (MPa)		1.6
Suitable temperature (°C)		≤80
Suitable medium		Water
Design standard: EN545		
4	Gasket	EPDM
3	Bolt and Nut	SS 316 Fasteners
2	Body	GGG50 FBE Min300µm
1	End Ring	GGG50 FBE Min300µm
NO.	Part Name	Material

NO	PIPE	RANGE	BOLT		H	B	D	A
	NORM	mm	L(mm)	n-φd	mm	mm	mm	mm
ITEM-1	DN80	88-103	130	4-M12	80	106	200	185
ITEM-2	DN100	109-128	130	4-M12	80	131	220	218
ITEM-3	DN125	138-153	140	4-M12	80	156	250	246
ITEM-4	DN150	159-182	140	4-M12	80	185	285	280
ITEM-5	DN200	218-235	140	4-M12	80	238	340	328
ITEM-6	DN250	272-289	150	6-M12	85	292	400	382
ITEM-7	DN300	315-332	150	6-M12	85	335	455	430

***Technical improvements reserved the right to DELTA.

**UNIVERSAL
FLANGE ADAPTOR**

FBE coating
RAL 5015

Ref. No.: 10123

SUPPLIER:
XUZHOU DELTA

